



Housing	Nickel-plated brass
Ball	Nickel-plated brass
Rotating handle	Plastic
Ball seal	PTFE
Stem seal	NBR
Medium temperature	-10 °C to 70 °C (short term up to 90 °C)
Ambient temperature	-10 °C to 70 °C (short term up to 90 °C)
Max. operating pressure	10 bar
Applications	Compressed air, water, oils, non-toxic gases
Thread material	Nickel-plated brass



375.00



375.01



375.10



375.51

Mini-Ball valve with rotating handle

Art. No.	Type No.	Thread	DN	a/f mm	L mm	A mm	B mm
103339	375.00	G 1/8 IT	8	20	39.0	22.0	27.2
103340	375.01	G 1/4 IT	8	20	39.0	22.0	27.2
103341	375.02	G 3/8 IT	8	20	42.0	22.0	27.2
103342	375.03	G 1/2 IT	10	24	47.0	22.0	29.5
134872	375.04	G 3/4 IT	13.5	30	54.0	22.0	32.0
103343	375.10	G 1/8 IT/ET	8	20	39.0	22.0	27.2
103344	375.11	G 1/4 IT/ET	8	20	39.0	22.0	27.2
103345	375.22	G 3/8 IT/ET	8	20	40.0	22.0	27.2
103346	375.33	G 1/2 IT/ET	10	24	45.0	22.0	29.5
134873	375.44	G 3/4 IT/ET	13.5	30	51.0	22.0	32.0
143656	375.51	G 1/4 ET	8	20	40.4	22.4	27.2
143657	375.52	G 3/8 ET	8	20	42.4	23.4	27.0
143658	375.53	G 1/2 ET	10	24	49.7	28.6	29.5