


Datasheet for: 136562


Rem. double threaded nipple, con. sealing, R 3/4 o., R 3/4 o.

Rem. double threaded nipple, con. seal. R 3/4 o., R 3/4 o. nickel-plated brass, Max. working pressure 25 bar, Max. oper. temp. 150°C . Suitable for air, water, oil, steam, etc.

Type number	MSN252L3434
Article number	136562
EAN/barcode	 4047322506571
Your price	12,67 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

L1	53.0 mm
Material	Nickel-plated brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	HK779
Thread 1	R 3/4
Thread 2	R 3/4
a/f	36 mm
a/f 1	14.0 mm

Variants

Article number	Thread 1	Thread 2	a/f	a/f 1	Price
136562	R 3/4	R 3/4	36 mm	14.0 mm	12,67 € / Stk
136561	R 1/2	R 1/2	27 mm	12.0 mm	5,66 € / Stk
136560	R 3/8	R 3/8	22 mm	8.0 mm	4,54 € / Stk

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>a/f</i>	<i>a/f 1</i>	<i>Price</i>
136559	R 1/4	R 3/8	19 mm	6.0 mm	3,85 € / Stk
136565	R 1 1/2	R 1 1/2	70 mm	24.0 mm	77,19 € / Stk
136558	R 1/4	R 1/4	19 mm	6.0 mm	2,83 € / Stk
136564	R 1 1/4	R 1 1/4	60 mm	22.0 mm	52,73 € / Stk
136557	R 1/8	R 1/4	15 mm	5.0 mm	2,49 € / Stk
136563	R 1	R 1	50 mm	19.0 mm	24,50 € / Stk
136566	R 2	R 2	80 mm	32.0 mm	111,63 € / Stk
136556	R 1/8	R 1/8	15 mm	5.0 mm	1,89 € / Stk