


Datasheet for: 137017


Push-in T-fitting L-shape »metallica«, rotating, G 1/2 o.

Push-in T-fitting L-shape »metallica«, rotating, G 1/2 o., for hose exterior \varnothing 14 mm, Working pressure max. 16 bar . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	862.012-14
Article number	137017
EAN/barcode	 4047322510011
Your price	12,74 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	14 mm
L1	33.0 mm
L2	67.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK714
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 1/2
a/f	20 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
137017	G 1/2	14 mm	20 mm	12,74 € / Stk
108947	G 3/8	10 mm	16 mm	8,30 € / Stk
108942	G 1/8	8 mm	13 mm	4,85 € / Stk
108945	G 1/4	10 mm	16 mm	7,41 € / Stk
108943	G 1/4	6 mm	13 mm	4,85 € / Stk
108941	G 1/8	6 mm	13 mm	4,85 € / Stk
108944	G 1/4	8 mm	13 mm	5,20 € / Stk
108940	G 1/8	4 mm	13 mm	5,14 € / Stk
108948	G 3/8	12 mm	16 mm	12,15 € / Stk
108949	G 1/2	12 mm	16 mm	12,31 € / Stk
108946	G 3/8	8 mm	13 mm	6,74 € / Stk
137016	G 3/8	14 mm	20 mm	12,31 € / Stk

More Pictures

