


## Datasheet for: 103906


**Mini bleeder valve, Brass, G 1/8, Trigger pressure 16 - 32 bar**

Mini bleeder valve, Brass, not component checked, Operating temp. -20°C to 180°C, PN 0.5-60 bar, G 1/8, Trigger pressure 16-32 bar . Manual adjustment of the blow-off pressure (lock nut). For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

Type number	218.15
Article number	103906
EAN/barcode	 4047322035040
Your price	7,50 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

C	27.0 mm
D	7.0 mm
Max. operating pressure	60 bar
Max. operating temperature	180 °C
Max. set pressure	32.0 bar
Min. operating pressure	0.5 bar
Min. operating temperature	-20 °C
Min. set pressure	16.0 bar
Page No.	HK360
Sealant	FKM
Thread	G 1/8
a/f	16 mm
blow-off rate	to 1600 l/min
do	3.0 mm

## Variants

Article number	Min. set pressure	Max. set pressure	blow-off rate	Price
103906	16.0 bar	32.0 bar	to 1600 l/min	7,50 € / Stk
103902	1.0 bar	4.0 bar	to 200 l/min	7,50 € / Stk
103903	3.0 bar	7.0 bar	to 350 l/min	7,50 € / Stk
103904	6.0 bar	12.0 bar	to 650 l/min	7,50 € / Stk
103905	10.0 bar	18.0 bar	to 870 l/min	7,50 € / Stk
103907	30.0 bar	60.0 bar	to 3000 l/min	7,50 € / Stk
103901	0.5 bar	1.0 bar	to 50 l/min	7,50 € / Stk

## More Pictures

