

Datasheet for: 106899


Throttle check valve, Supply air throttle, Thread.conn.G1/8i.,G1/8

Throttle check valve, Supply air throttle (»V«) Threaded connection G 1/8 i., G 1/8, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number 339.018-1/8

Article number 106899

EAN/barcode



4047322180887

Your price 12,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	42.4 mm
C	16.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
Connection	G 1/8 female thread
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK499
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
a/f	14 mm

Variants

Article number	Thread	Connection	a/f	Price
106899	G 1/8	G 1/8 female thread	14 mm	12,81 € / Stk
106900	G 1/4	G 1/4 female thread	17 mm	13,29 € / Stk
106901	G 3/8	G 3/8 female thread	20 mm	21,09 € / Stk
106898	M5	M5 female thread	8 mm	11,76 € / Stk

More Pictures

