


Datasheet for: 103911


Mini bleeder valve, Brass, G 1/4, Trigger pressure 6 - 12 bar

Mini bleeder valve, Brass, not component checked, Operating temp. -20°C to 180°C, PN 0.5-60 bar, G 1/4, Trigger pressure 6-12 bar . Manual adjustment of the blow-off pressure (lock nut). For compressed air and non-toxic, non-flammable gases, cannot be used for liquids due to free blow-off, not suitable for steam.

Type number	218.23
Article number	103911
EAN/barcode	 4047322035118
Your price	7,50 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

C	27.0 mm
D	7.0 mm
Max. operating pressure	60 bar
Max. operating temperature	180 °C
Max. set pressure	12.0 bar
Min. operating pressure	0.5 bar
Min. operating temperature	-20 °C
Min. set pressure	6.0 bar
Page No.	HK360
Sealant	FKM
Thread	G 1/4
a/f	16 mm
blow-off rate	to 650 l/min
do	3.0 mm

Variants

<i>Article number</i>	<i>Min. set pressure</i>	<i>Max. set pressure</i>	<i>blow-off rate</i>	<i>Price</i>
103911	6.0 bar	12.0 bar	to 650 l/min	7,50 € / Stk
103909	1.0 bar	4.0 bar	to 200 l/min	7,50 € / Stk
103910	3.0 bar	7.0 bar	to 350 l/min	7,50 € / Stk
103912	10.0 bar	18.0 bar	to 870 l/min	7,50 € / Stk
103913	16.0 bar	32.0 bar	to 1600 l/min	7,50 € / Stk
103914	30.0 bar	60.0 bar	to 3000 l/min	7,50 € / Stk
103908	0.5 bar	1.0 bar	to 50 l/min	7,50 € / Stk

More Pictures

