


Datasheet for: 113003


T-piece 134, IT/IT/ET, Rp 1 i., R 1 o., Rp 1 i.

T-piece 134, IT/IT/ET, Rp 1 i., R 1 o., Rp 1 i., Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFT 134-10
Article number	113003
EAN/barcode	 4047322395861
Your price	7,51 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK858
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread 1	Rp 1
Thread 2	R 1
Thread 3	Rp 1

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Thread 3</i>	<i>Price</i>
113003	Rp 1	R 1	Rp 1	7,51 € / Stk
113006	Rp 2	R 2	Rp 2	23,00 € / Stk
113005	Rp 1 1/2	R 1 1/2	Rp 1 1/2	14,51 € / Stk
113004	Rp 1 1/4	R 1 1/4	Rp 1 1/4	11,68 € / Stk
113002	Rp 3/4	R 3/4	Rp 3/4	5,21 € / Stk
113001	Rp 1/2	R 1/2	Rp 1/2	3,74 € / Stk