

## Datasheet for: 117928


**Distributor, 2 quick-connect coupl. I.D. 7.2, G 3/8 IT, »R26EMS«**

Distributor with 2 quick-connect couplings I.D. 7.2, »R26EMS«, Bright brass, G 3/8 IT, Operating pressure - 35 bar . 2-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2. Available with threaded connection inside or outside.

Type number	245.37-E
Article number	117928
EAN/barcode	 4047322061186
Your price	12,84 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Comprising distributor	Brass with a bare metal surface, G 3/8 IT
Connection	G 3/8 IT
Couplings	DN 7.2, brass with a bare metal surface, G 3/8 ET
Height	69.0 mm
Housing	Brass with a bare metal surface
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure	35 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK534
Page No. AS	Web-Only
Page No. TS	TS007
Sealant	Industrial adhesives, medium strength
Securing	Industrial adhesives, medium strength
Width	89.0 mm

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
117928	G 3/8 IT	12,84 € / Stk
117929	G 1/2 IT	15,61 € / Stk
117927	G 1/4 IT	12,84 € / Stk

## More Pictures

