

Datasheet for: 158909


Adjustable male conn., M18x1.5o., Pipe ext.Ø15, galvanised steel

Adjustable male connector, with cone seal, M18x1.5 o., Pipe exterior Ø 15, PN 315, a/f1 27, a/f2 24, galvanised steel .

| | |
|----------------|--|
| Type number | EGEM1815LSTKEG |
| Article number | 158909 |
| EAN/barcode |  4047322635714 |
| Your price | 7,54 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | | |
|---------------|-----|-----------------------------|
| Female thread | nut | M22x1.5 |
| L1 | | 43.5 mm |
| L2 | | 12.0 mm |
| Material | | Galvanised steel (DIN 2353) |
| PN | | 315 bar |
| Page No. | | HK824 |
| Thread | | M18x1.5 |
| Tube O.D. | | 15 mm |
| a/f 1 | | 27.0 mm |
| a/f 2 | | 24.0 mm |

Variants

| Article number | Female nut thread | Thread | Tube O.D. | PN | a/f 1 | a/f 2 | Price |
|----------------|-------------------|---------|-----------|---------|---------|---------|--------------|
| 158909 | M22x1.5 | M18x1.5 | 15 mm | 315 bar | 27.0 mm | 24.0 mm | 7,54 € / Stk |
| 158910 | M26x1.5 | M22x1.5 | 18 mm | 315 bar | 32.0 mm | 27.0 mm | 8,54 € / Stk |
| 158906 | M14x1.5 | M12x1.5 | 8 mm | 315 bar | 17.0 mm | 17.0 mm | 5,58 € / Stk |

Variants

| Article number | Female nut thread | Thread | Tube O.D. | PN | a/f 1 | a/f 2 | Price |
|----------------|-------------------|---------|-----------|---------|---------|---------|---------------|
| 158907 | M16x1.5 | M14x1.5 | 10 mm | 315 bar | 19.0 mm | 19.0 mm | 5,77 € / Stk |
| 158912 | M36x2.0 | M33x2.0 | 28 mm | 160 bar | 41.0 mm | 41.0 mm | 21,09 € / Stk |
| 158905 | M12x1.5 | M10x1.0 | 6 mm | 315 bar | 14.0 mm | 14.0 mm | 5,43 € / Stk |
| 158911 | M30x2.0 | M26x1.5 | 22 mm | 160 bar | 36.0 mm | 32.0 mm | 12,88 € / Stk |
| 158908 | M18x1.5 | M16x1.5 | 12 mm | 315 bar | 22.0 mm | 22.0 mm | 6,36 € / Stk |

More Pictures

