


## Datasheet for: 106875


**Throttle check valve, Supply air throttle (»V«) M5 i., M5**

Throttle check valve, Supply air throttle (»V«) Threaded connection M5 i., M5, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Type number	357.005-M5
-------------	------------

Article number	106875
----------------	--------

EAN/barcode	 4047322181730
-------------	--

Your price	9,72 € / Stk
------------	--------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	24.5 mm
C	11.5 mm
Captive seals	Polyamide (glass fibre-reinforced)
Connection	M5 IG
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK498
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Connection</i>	<i>a/f</i>	<i>Price</i>
106875	M5	M5 IG	8 mm	9,72 € / Stk
106876	G 1/8	G 1/8 IG	14 mm	9,72 € / Stk
106877	G 1/4	G 1/4 IG	17 mm	10,54 € / Stk
106878	G 3/8	G 3/8 IG	20 mm	18,90 € / Stk

## More Pictures

