

Datasheet for: 106876


Throttle check valve, Supply air throttle (»V«) G 1/8 i., G 1/8

Throttle check valve, Supply air throttle (»V«) Threaded connection G 1/8 i., G 1/8, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

| | |
|-------------|-------------|
| Type number | 357.018-1/8 |
|-------------|-------------|

| | |
|----------------|--------|
| Article number | 106876 |
|----------------|--------|

| | |
|-------------|--|
| EAN/barcode |  4047322181785 |
|-------------|--|

| | |
|------------|--------------|
| Your price | 9,72 € / Stk |
|------------|--------------|

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|------------------------------------|
| Adjusting screw | Nickel-plated brass |
| B | 32.0 mm |
| C | 16.0 mm |
| Captive seals | Polyamide (glass fibre-reinforced) |
| Connection | G 1/8 IG |
| Hollow bolt | Nickel-plated brass |
| Internal parts | Brass with a bare metal surface |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Page No. | HK498 |
| Pivoting arm | Nickel-plated brass |
| Sealant | NBR |
| Thread | G 1/8 |
| a/f | 14 mm |

Variants

| Article number | Thread | Connection | a/f | Price |
|----------------|--------|------------|-------|---------------|
| 106876 | G 1/8 | G 1/8 IG | 14 mm | 9,72 € / Stk |
| 106877 | G 1/4 | G 1/4 IG | 17 mm | 10,54 € / Stk |
| 106875 | M5 | M5 IG | 8 mm | 9,72 € / Stk |
| 106878 | G 3/8 | G 3/8 IG | 20 mm | 18,90 € / Stk |

More Pictures

