

Datasheet for: 106879



Throttle check valve, Supply air throttle, quick conn. Hose 4/2.5, M5

Throttle check valve, Supply air throttle (»V«) quick connector Hose 4/2.5, M5, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Type number 357.005-4

Article number 106879

EAN/barcode



4047322181617

Your price 9,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	24.5 mm
C	18.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	4 / 2.5 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK498
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

Variants

Article number	Thread	For hose	a/f	Price
106879	M5	4 / 2.5 mm	8 mm	9,72 € / Stk
106880	M5	5 / 3 mm	8 mm	9,72 € / Stk
106881	M5	6 / 4 mm	8 mm	9,72 € / Stk
106882	G 1/8	5 / 3 mm	14 mm	9,72 € / Stk
106883	G 1/8	6 / 4 mm	14 mm	9,72 € / Stk
106884	G 1/8	8 / 6 mm	14 mm	9,72 € / Stk
106885	G 1/4	6 / 4 mm	17 mm	10,02 € / Stk
106886	G 1/4	8 / 6 mm	17 mm	10,02 € / Stk
106887	G 1/4	10 / 8 mm	17 mm	10,54 € / Stk
106888	G 3/8	10 / 8 mm	20 mm	16,89 € / Stk

More Pictures

