

Datasheet for: 108964


**Push-in T-fitting »metallica« rotating, G 1/8 o., hose exterior Ø6**

Push-in T-fitting »metallica«, rotating, G 1/8 o., for hose exterior Ø 6 mm, Working pressure max. 16 bar, nickel-plated brass . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	864.018-6
-------------	-----------

Article number	108964
----------------	--------

EAN/barcode	 4047322282260
-------------	--



Your price	7,64 € / Stk
------------	--------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Clamping ring	Stainless steel
For tube O.D.	6 mm
L1	46.0 mm
L2	28.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK715
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 1/8
a/f	14 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
108964	G 1/8	6 mm	14 mm	7,64 € / Stk
108965	G 1/4	6 mm	17 mm	8,09 € / Stk
108963	G 1/8	4 mm	14 mm	7,80 € / Stk

## More Pictures

