

## Datasheet for: 106890


**Throttle check valve, Supply air throttle push-in conn. M5, Hose 6**

Throttle check valve, Supply air throttle (»V«) push-in connector hose 6, M5, PN max. 10 bar, Temperature °C to 70 °C. For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

Type number	342.005-6
Article number	106890
EAN/barcode	 4047322180665
Your price	9,72 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	24.5 mm
C	21.7 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	6 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK498
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

## Variants

Article number	Thread	For hose	a/f	Price
106890	M5	6 mm	8 mm	9,72 € / Stk
106889	M5	4 mm	8 mm	9,72 € / Stk
106891	G 1/8	4 mm	14 mm	9,72 € / Stk
106892	G 1/8	6 mm	14 mm	9,72 € / Stk
106893	G 1/8	8 mm	14 mm	9,72 € / Stk
106894	G 1/4	6 mm	17 mm	10,54 € / Stk
106895	G 1/4	8 mm	17 mm	10,77 € / Stk
106896	G 1/4	10 mm	17 mm	11,03 € / Stk
106897	G 3/8	10 mm	20 mm	16,89 € / Stk

## More Pictures

