

Datasheet for: 106893


Throttle check valve, Supply air throttle push-in conn.G1/8,Hose 8

Throttle check valve, Supply air throttle (»V«) push-in connector hose 8, G 1/8, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

| | |
|----------------|--|
| Type number | 342.018-8 |
| Article number | 106893 |
| EAN/barcode |  4047322180788 |
| Your price | 9,72 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|------------------------------------|
| Adjusting screw | Nickel-plated brass |
| B | 32.0 mm |
| C | 23.7 mm |
| Captive seals | Polyamide (glass fibre-reinforced) |
| For hose | 8 mm |
| Hollow bolt | Nickel-plated brass |
| Internal parts | Brass with a bare metal surface |
| Max. operating pressure | 10 bar |
| Max. temperature range | 70 °C |
| Page No. | HK498 |
| Pivoting arm | Nickel-plated brass |
| Sealant | NBR |
| Thread | G 1/8 |
| a/f | 14 mm |

Variants

| Article number | Thread | For hose | a/f | Price |
|----------------|--------|----------|-------|---------------|
| 106893 | G 1/8 | 8 mm | 14 mm | 9,72 € / Stk |
| 106889 | M5 | 4 mm | 8 mm | 9,72 € / Stk |
| 106890 | M5 | 6 mm | 8 mm | 9,72 € / Stk |
| 106891 | G 1/8 | 4 mm | 14 mm | 9,72 € / Stk |
| 106892 | G 1/8 | 6 mm | 14 mm | 9,72 € / Stk |
| 106894 | G 1/4 | 6 mm | 17 mm | 10,54 € / Stk |
| 106895 | G 1/4 | 8 mm | 17 mm | 10,77 € / Stk |
| 106896 | G 1/4 | 10 mm | 17 mm | 11,03 € / Stk |
| 106897 | G 3/8 | 10 mm | 20 mm | 16,89 € / Stk |

More Pictures

