

## Datasheet for: 106934


**Throttle check valve, Discharge throttle (»C«) push-in connector**

Throttle check valve, Discharge throttle (»C«) push-in connector hose 4, M5, PN max. 10 bar, Temperature °C to 70 °C . For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted.

Type number	343.005-4
Article number	106934
EAN/barcode	 4047322180795
Your price	9,72 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjusting screw	Nickel-plated brass
B	24.5 mm
C	18.6 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	4 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK500
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

## Variants

Article number	Thread	For hose	a/f	Price
106934	M5	4 mm	8 mm	9,72 € / Stk
106935	M5	6 mm	8 mm	9,72 € / Stk
106936	G 1/8	4 mm	14 mm	9,72 € / Stk
106937	G 1/8	6 mm	14 mm	9,72 € / Stk
106938	G 1/8	8 mm	14 mm	9,72 € / Stk
106939	G 1/4	6 mm	17 mm	10,60 € / Stk
106940	G 1/4	8 mm	17 mm	10,77 € / Stk
106941	G 1/4	10 mm	17 mm	11,23 € / Stk
106942	G 3/8	10 mm	20 mm	16,89 € / Stk

## More Pictures

