

Datasheet for: 106969



Throttle valve, Both sides throttling (»B«) quick connector, M5

Throttle valve, Both sides throttling (»B«) quick connector
 Hose 4/2.5, M5, PN max. 10 bar, Temperature °C to 70 °C .
 For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.

Type number	359.005-4
-------------	-----------

Article number	106969
----------------	--------

EAN/barcode



4047322181020

Your price	9,72 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	24.5 mm
C	18.0 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	4 / 2.5 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK502
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	M5
a/f	8 mm

Variants

Article number	Thread	For hose	a/f	Price
106969	M5	4 / 2.5 mm	8 mm	9,72 € / Stk
106970	M5	5 / 3 mm	8 mm	9,72 € / Stk
106971	M5	6 / 4 mm	8 mm	9,72 € / Stk
106972	G 1/8	5 / 3 mm	14 mm	9,72 € / Stk
106973	G 1/8	6 / 4 mm	14 mm	9,72 € / Stk
106974	G 1/8	8 / 6 mm	14 mm	9,72 € / Stk
106975	G 1/4	6 / 4 mm	17 mm	10,08 € / Stk
106976	G 1/4	8 / 6 mm	17 mm	10,08 € / Stk
106977	G 1/4	10 / 8 mm	17 mm	10,60 € / Stk
106978	G 3/8	10 / 8 mm	20 mm	16,89 € / Stk

More Pictures

