


- Adjustable with slotted-head screwdriver -

For regulation of a cylinder piston speed at both ends and control of flow rates.

Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly.

Compact type of construction, also ideal where space is restricted.



Operating pressure:

Temperature range:

Hollow bolt, pivoting arm, adjusting screw:

Valve trim:

Lip seal, O-ring:

Captive seals:

Max. 10 bar


0 °C to +70 °C

Nickel-plated brass

Brass with a bare metal surface

NBR


Polyamide (glass fibre-reinforced)



359.005-M5

Bidirectional flow control valves, air restriction at both ends (»B«), screw connection

Type No.	Art. No.	Thread	For pipe mm	a/f mm	B mm	C mm
359.005-M5	106964	M5	M5 female thread	8	24.5	11.5
359.018-1/8	106965	G 1/8	G 1/8 female thread	14	32.0	16.0
359.014-1/4	106966	G 1/4	G 1/4 female thread	17	40.0	22.0
359.038-3/8	106967	G 3/8	G 3/8 female thread	20	50.0	26.0
359.012-1/2	106968	G 1/2	G 1/2 female thread	26	61.0	32.0



359.014-6



359.005-6

Bidirectional flow control valves, air restriction at both ends (»B«), quick-lock screw fitting

Type No.	Art. No.	Thread	For pipe mm	a/f mm	B mm	C mm
359.005-4	106969	M5	4/2.5	8	24.5	18.0
359.005-5	106970	M5	5/3	8	24.5	19.0
359.005-6	106971	M5	6/4	8	24.5	19.0
359.018-5	106972	G 1/8	5/3	14	32,0	23.0
359.018-6	106973	G 1/8	6/4	14	32,0	25.0
359.018-8	106974	G 1/8	8/6	14	32,0	25.0
359.014-6	106975	G 1/4	6/4	17	40,0	26.5
359.014-8	106976	G 1/4	8/6	17	40,0	27.5
359.014-10	106977	G 1/4	10/8	17	40,0	28.5
359.038-10	106978	G 3/8	10/8	20	50.0	30.5