


Datasheet for: 133636

Bracket 92, 90°, Rp 2 IT, R 2 ET, black malleable iron fitting


Bracket 92, 90°, Rp 2 IT, R 2 ET, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 92-20-S
Article number	133636
EAN/barcode	 4047322480154
Your price	7,70 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK866
Standard	acc. ISO 7-1
thread	Black
Surface	Rp/R 2
Thread	

Variants

Article number	Thread	Price
----------------	--------	-------

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133636	Rp/R 2	7,70 € / Stk
133637	Rp/R 2 1/2	18,89 € / Stk
133635	Rp/R 1 1/2	5,60 € / Stk
133630	Rp/R 3/8	1,26 € / Stk
133634	Rp/R 1 1/4	4,06 € / Stk
133632	Rp/R 3/4	1,46 € / Stk
133631	Rp/R 1/2	1,00 € / Stk
133633	Rp/R 1	2,26 € / Stk
133629	Rp/R 1/4	1,26 € / Stk