

Datasheet for: 106982



Throttle valve, Both sides throttling (»B«) Push-in connector

Throttle valve, Both sides throttling (»B«) push-in connector hose 6, G 1/8, PN max. 10 bar, Temperature °C to 70 °C . For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. Compact type of construction, also ideal where space is restricted.

Type number	344.018-6
-------------	-----------

Article number	106982
----------------	--------

EAN/barcode



4047322181563

Your price	9,72 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	32.0 mm
C	22.7 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	6 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK502
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/8
a/f	14 mm

Variants

Article number	Thread	For hose	a/f	Price
106982	G 1/8	6 mm	14 mm	9,72 € / Stk
106979	M5	4 mm	8 mm	9,72 € / Stk
106980	M5	6 mm	8 mm	9,72 € / Stk
106981	G 1/8	4 mm	14 mm	9,72 € / Stk
106983	G 1/8	8 mm	14 mm	9,72 € / Stk
106984	G 1/4	6 mm	17 mm	10,60 € / Stk
106985	G 1/4	8 mm	17 mm	10,77 € / Stk
106986	G 1/4	10 mm	17 mm	11,23 € / Stk
106987	G 3/8	10 mm	20 mm	16,89 € / Stk

More Pictures

