


## Datasheet for: 133781


**Reducing sleeve 246, Rp 1 1/2 IT, R 1 ET**

Reducing sleeve 246, Rp 1 1/2 IT, R 1 ET, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFM 246-11210-S
Article number	133781
EAN/barcode	 4047322481205
Your price	5,50 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK870
Standard	acc. ISO 7-1
thread	Black
Surface	Rp 1 1/2
Thread 1	R 1
Thread 2	

## Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Price</i>
133781	Rp 1 1/2	R 1	5,50 € / Stk
133782	Rp 2	R 1	9,22 € / Stk
133786	Rp 1 1/2	R 3/4	5,50 € / Stk
133780	Rp 1 1/4	R 1	4,54 € / Stk
133783	Rp 2	R 1 1/4	7,76 € / Stk
133777	Rp 1	R 1/2	3,23 € / Stk
133778	Rp 1	R 3/4	3,40 € / Stk
133774	Rp 1/2	R 1/4	1,79 € / Stk
133785	Rp 2 1/2	R 2	13,26 € / Stk
133773	Rp 3/8	R 1/4	1,79 € / Stk
133779	Rp 1 1/4	R 3/4	4,54 € / Stk
133784	Rp 2	R 1 1/2	7,93 € / Stk
133776	Rp 3/4	R 1/2	2,43 € / Stk
133775	Rp 1/2	R 3/8	1,79 € / Stk