


Datasheet for: 140995


Strainer nickel-plated brass, G 1/2, DN 15, mesh width 0.5 mm

Dirt strainer, nickel-plated brass, Sieve insert mesh width 0.5 mm, Operating temp. -20 °C to 110 °C, G 1/2, DN 15, PN max. 20 bar . Suitable for domestic water services, heating and air conditioning plants or compressed air systems. Not suitable for steam.

Type number	60-3 N
Article number	140995
EAN/barcode	 4047322547215
Your price	7,71 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

C	40.0 mm
DN	15.0
Head piece	Nickel-plated brass
Housing	Nickel-plated brass
L	58.0 mm
Max. operating pressure	20 bar
Max. operating temperature	110 °C
Mesh size	0.5 mm
Min. operating temperature	-20 °C
Page No.	HK370
Screen	Stainless steel
Sealant	NBR O-ring
Standard thread	G thread acc. to ISO 228-1, tolerance class B
Thread	G 1/2
a/f 1	25.0 mm
a/f 2	20.0 mm

Variants

Article number	Thread	DN	a/f 1	a/f 2	Price
140995	G 1/2	15.0	25.0 mm	20.0 mm	7,71 € / Stk
140998	G 1 1/4	32.0	47.0 mm	36.0 mm	27,93 € / Stk
140994	G 1/4	8.0	18.0 mm	20.0 mm	7,29 € / Stk
137836	G 3/8	10.0	21.0 mm	20.0 mm	7,29 € / Stk
140997	G 1	25.0	38.0 mm	32.0 mm	18,84 € / Stk
141000	G 2	50.0	67.0 mm	46.0 mm	60,75 € / Stk
140996	G 3/4	20.0	31.0 mm	27.0 mm	12,24 € / Stk
140999	G 1 1/2	40.0	54.0 mm	38.0 mm	36,43 € / Stk

More Pictures

