

Datasheet for: 107852


Jaw coupling with exterior thread, G 1/2, DN 13

Jaw coupling with ET, G 1/2, DN 13, Malleable cast iron, galvanised and yellow passivated, Operating pressure max. 10 bar . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

| | |
|----------------|--|
| Type number | KA 12 |
| Article number | 107852 |
| EAN/barcode |  4047322258821 |
| Your price | 5,51 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|--|
| Claw distance | 42 mm |
| DN | 13.0 |
| H | 63.0 mm |
| L | 48.0 mm |
| Material | Malleable iron, zinc plated and yellow chromated |
| Max. operating pressure | 10 bar |
| Max. operating temperature | 95 °C |
| Min. operating temperature | -40 °C |
| Page No. | HK611 |
| Sealant | NBR |
| Thread | G 1/2 |
| a/f | 27 mm |

Variants

| <i>Article number</i> | <i>DN</i> | <i>Thread</i> | <i>a/f</i> | <i>Price</i> |
|-----------------------|-----------|---------------|------------|--------------|
| 107852 | 13.0 | G 1/2 | 27 mm | 5,51 € / Stk |
| 107851 | 8.5 | G 3/8 | 27 mm | 6,27 € / Stk |
| 107853 | 17.0 | G 3/4 | 32 mm | 5,08 € / Stk |
| 107854 | 20.0 | G 1 | 40 mm | 5,84 € / Stk |