


## Datasheet for: 103205


**Ball valve standard design, red steel lever, IT/ET, G 1/2**

Ball valve standard design, red steel lever, IT/ET, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 1/2, PN max. 40 bar . Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

Type number	331.04-R
Article number	103205
EAN/barcode	 4047322278225
Your price	13,16 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	85.0 mm
B	44.1 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	15.0
E	9.5 mm
F	9.5 mm
Hand lever	Steel, with plastic coating
L	59.8 mm
Material	Nickel-plated brass
Max. operating temperature	90 °C
Min. operating temperature	-15 °C
PN	40 bar
Page No.	HK271
Standard thread	G thread acc. to DIN EN ISO 228-1
Stem seal	2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE
Thread	G 1/2
Thread material	Brass with a bare metal surface

## Variants

Article number	Thread	DN	Price
103205	G 1/2	15.0	13,16 € / Stk
103208	G 1 1/4	32.0	40,42 € / Stk
103206	G 3/4	20.0	17,94 € / Stk
103204	G 3/8	10.0	12,35 € / Stk
103207	G 1	25.0	25,17 € / Stk
103203	G 1/4	8.0	11,76 € / Stk
103210	G 2	50.0	90,51 € / Stk
103209	G 1 1/2	40.0	59,41 € / Stk

## More Pictures

