


Datasheet for: 107773


GEKA threaded piece, rigid, bright brass, G 1 1/2 exterior

GEKA threaded piece, rigid, bright brass, G 1 1/2 exterior, Operating pressure max. 40 bar, Medium / ambient temp. -10 °C to 90 °C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 116 A
Article number	107773
EAN/barcode	 4047322133067
Your price	7,78 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1 1/2 ET
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK607
Sealant	NBR

Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107773	G 1 1/2 ET	7,78 € / Stk
107767	G 1/4 ET	6,27 € / Stk
107768	G 3/8 ET	4,39 € / Stk
107769	G 1/2 ET	3,96 € / Stk
107770	G 3/4 ET	4,13 € / Stk
107771	G 1 ET	4,26 € / Stk
107772	G 1 1/4 ET	6,15 € / Stk