


Datasheet for: 107846


Jaw coupling with hose connection, I.D. 19 (3/4") with brass seal

Jaw coupling with hose connection, I.D. 19 (3/4"), with brass seal, Malleable cast iron, galvanised/yellow passivated, max. 10 bar . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KT 19 M
Article number	107846
EAN/barcode	 4047322258593
Your price	7,78 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	15.0
For hose I.D.	19 (3/4")
H	63.0 mm
L	82.9 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK611
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Price</i>
107846	15.0	19 (3/4")	7,78 € / Stk
107847	19.0	25 (1")	9,92 € / Stk
107845	8.5	13 (1/2")	8,95 € / Stk