

Datasheet for: 107953



Tempered coupl. DN 9, Taps 13 mm, Blocking valve, Sleeve straight

Tempered coupling DN 9, Taps 13 mm, Blocking valve, Brass, Hose sleeve straight, Operating pressure max. 15 bar . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	280.01
Article number	107953
EAN/barcode	 4047322258678
Your price	13,16 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Hose connection	13 mm
Hose stem type	straight
Length	61.5 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK617
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel

Variants

Article number	Hose stem type	Price
107953	straight	13,16 € / Stk
107955	90°	18,53 € / Stk
107954	45°	18,53 € / Stk