

Datasheet for: 108029


Kamlok quick-connect socket, C type, Alu, I.D. 38, for plug Ø 53

Kamlok quick-connect socket, Hose supports, C type, Aluminium, Hose I.D. 38, for plug Ø 53 mm, Operating pressure max. 16 bar . Coupling system for quick and easy connection of two hoses or for joining one hose to a machine connection. A male part and a female part are joined together by shifting the handles. There is no need to turn the hose! Kamlok couplings are used for a wide range of applications in industrial plant and mechanical engineering, tank and container construction, the chemical industry, food processing, mining, refuelling systems, defence technology, etc.

Type number	1112.112
Article number	108029
EAN/barcode	 4047322403061
Your price	9,84 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	87.4 mm
C	116.5 mm
For hose I.D.	38
For plug Ø	53.0 mm
Max. operating pressure	16 bar
Max. temperature range	68 °C
Page No.	HK621
Sealant	NBR, resistant to oils and benzine

Variants

Article number	For hose I.D.	For plug Ø	Price
108029	38	53.0 mm	9,84 € / Stk
108032	75	92.0 mm	19,79 € / Stk
108031	63	76.0 mm	14,50 € / Stk
108030	50	63.0 mm	12,13 € / Stk
108028	32	45.0 mm	8,93 € / Stk
108027	25	37.0 mm	6,52 € / Stk
108033	100	120.0 mm	26,85 € / Stk
108026	19	32.0 mm	5,99 € / Stk

More Pictures

