

Datasheet for: 107006


Throttle valve, Both sides throttling (»B«) Push-in connector

Throttle valve, Both sides throttling (»B«) push-in connector hose 6, G 1/4, PN max. 10 bar, Temperature °C to 70 °C . For regulation of a cylinder piston speed at both ends and control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece for mounting directly. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Type number	338.014-6
-------------	-----------

Article number	107006
----------------	--------

EAN/barcode	
-------------	--



4047322180658

Your price	13,29 € / Stk
------------	---------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjusting screw	Nickel-plated brass
B	51.0 mm
C	24.2 mm
Captive seals	Polyamide (glass fibre-reinforced)
For hose	6 mm
Hollow bolt	Nickel-plated brass
Internal parts	Brass with a bare metal surface
Max. operating pressure	10 bar
Max. temperature range	70 °C
Page No.	HK503
Pivoting arm	Nickel-plated brass
Sealant	NBR
Thread	G 1/4
a/f	17 mm

Variants

Article number	Thread	For hose	a/f	Price
107006	G 1/4	6 mm	17 mm	13,29 € / Stk
107002	M5	4 mm	8 mm	12,23 € / Stk
107003	G 1/8	4 mm	14 mm	11,61 € / Stk
107004	G 1/8	6 mm	14 mm	11,61 € / Stk
107005	G 1/8	8 mm	14 mm	13,29 € / Stk
107007	G 1/4	8 mm	17 mm	13,29 € / Stk
107008	G 1/4	10 mm	17 mm	13,87 € / Stk

More Pictures

