


Datasheet for: 107724

Plug nipple without pressure eliminator, Series A, I.D. 13


Plug nipple without pressure eliminator, Series A, I.D. 13, hardened, galvanised steel, G 1/2 IT, PN max. 250 bar . Acc. to ISO 7241-1, A Series. This coupling series combines an extremely small pressure drop with maximum hydraulic power transmission. Interchangeable with all couplings and plugs manufactured according to the above standard. The patented pressure eliminator permits disconnection even if back pressure has built up (up to 200 bar). The pressure eliminator can be used in all applications where there is a risk of pressure build-up after the line has been separated. It allows effortless connection under pressure. The mating part must be pressureless in order for the eliminator to function optimally. Areas of application: Agricultural machines, construction machines, municipal engineering, transportation engineering, industrial plant.

Type number	242.51 A
Article number	107724
EAN/barcode	 4047322056939
Your price	13,30 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 1/2 IT
Housing	Brass
Length	41.0 mm
Max. operating pressure	250 bar
Max. operating temperature	100 °C
Min. operating temperature	-30 °C
Page No.	HK605
Page No. SK	SK088
Sealant	NBR
Spring	Stainless steel
Unlocking sleeve	Nickel-plated brass
Valve	Hard drawn brass
a/f	27 mm

More Pictures

