


Datasheet for: 103150


Safety ball valve, lockable, Venting hole, Rp 3/8

Safety ball valve, lockable, Venting hole M5, nickel-plated brass, Operating temp. -10 °C to 100 °C, Rp 3/8, DN 10, PN max. 14 bar . Safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications. The valve shuts off the supply line and bleeds the application area. Lockable hand lever in closed position ensures a high protection against manipulation.

Type number	321.03
Article number	103150
EAN/barcode	 4047322366199
Your price	13,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	96.0 mm
B	49.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
DN	10.0
Hand lever	Steel - PVC coated
Housing	Nickel-plated brass
L	45.0 mm
Max. operating pressure	14 bar
Max. operating temperature	100 °C
Min. operating temperature	-10 °C
Page No.	HK282
Page No. SF	SF045
Relief port	M5
Standard thread	Rp thread acc. to EN 10226
Stem seal	FKM
Thread	Rp 3/8
Thread material	Nickel-plated brass

Variants

Article number	Thread	Relief port	DN	Price
103150	Rp 3/8	M5	10.0	13,34 € / Stk
103153	Rp 1	M5	25.0	31,58 € / Stk
103152	Rp 3/4	M5	20.0	20,00 € / Stk
103151	Rp 1/2	M5	15.0	14,97 € / Stk
103154	Rp 1 1/4	G 1/4	32.0	75,18 € / Stk
103156	Rp 2	G 1/4	50.0	153,85 € / Stk
103149	Rp 1/4	M5	8.0	13,34 € / Stk
103155	Rp 1 1/2	G 1/4	40.0	100,96 € / Stk

More Pictures

