


Datasheet for: 103335


Mini ball valve, Sand blasted, Manual lever, G 1/2 IT

Mini ball valve, Sand blasted, nickel-plated brass, Manual lever, Medium/ambient temp. -10 °C to 90 °C, G 1/2 IT, PN max. 10 bar .

Type number	374.03
Article number	103335
EAN/barcode	 4047322080941
Your price	10,02 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	68.5 mm
Applications	Compressed air, water, oils, non-toxic gases
Ball	Nickel-plated brass
Ball seal	PTFE
DN	10.0
E	12.5 mm
F	10.5 mm
Hand lever	Plastic
Housing	Nickel-plated brass
L	47.0 mm
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	10 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK285
Stem seal	FKM
Thread	G 1/2 IT
Thread material	Nickel-plated brass
a/f	25 mm

Variants

Article number	Thread	a/f	DN	Price
103335	G 1/2 IT	25 mm	10.0	10,02 € / Stk
103333	G 1/4 IT	21 mm	8.0	8,96 € / Stk
103334	G 3/8 IT	21 mm	8.0	8,96 € / Stk
103336	G 1/4 IT/ET	20 mm	8.0	8,96 € / Stk
103337	G 3/8 IT/ET	21 mm	8.0	8,96 € / Stk
103338	G 1/2 IT/ET	25 mm	10.0	10,02 € / Stk

More Pictures

