


Datasheet for: 107512



Quick-connect coupling I.D. 7.2, locking on both sides, I.D. 6

Quick-connect coupl. I.D. 7.2, locking on both sides, Bright brass, Sleeve I.D. 6, Operat. pressure 0-35 bar, Temp. -20°C to 100°C. Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping. Areas of application: Pneumatic system, machine and plant engineering, Measurement, monitoring and control systems, Manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology, aerospace.

Type number	243.44-B
Article number	107512
EAN/barcode	 4047322059688
Your price	10,03 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	I.D. 6
DN	7.2
Flow rate	700 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	58.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK558
Page No. SK	SK040
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel

Valve body
 a/f

 Brass with a bare metal surface
 21 mm

Variants

Article number	Connection	Price
107512	I.D. 6	10,03 € / Stk
107514	I.D. 9	10,03 € / Stk
107516	I.D. 13	10,10 € / Stk
107513	I.D. 8	12,93 € / Stk
107515	I.D. 10	12,93 € / Stk

More Pictures

