

Datasheet for: 107070

Quick-connect coupling I.D. 2.7, bright brass, G 1/8 ET


Quick-connect coupling I.D. 2.7, bright brass, G 1/8 ET, Operating pressure - 35 bar, Med. / ambient temp. -20°C to 100°C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

Type number	243.08/2
Article number	107070
EAN/barcode	 4047322057929
Your price	5,69 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	G 1/8 ET
DN	2.7
Flow rate	165 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	28.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK518
Page No. SK	SK005
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface

Spring
 Valve body
 a/f

Stainless steel
 Brass with a bare metal surface
 11 mm

Variants

Article number	Connection	Length	a/f	Price
107070	G 1/8 ET	28.0 mm	11 mm	5,69 € / Stk
107069	M5 ET	26.0 mm	9 mm	5,46 € / Stk

More Pictures

