

Datasheet for: 110792


Straight screw-on fitting G 1/2 i., for hose 6/8 mm, AF 27, PA

Straight screw-on fitting G 1/2 i., for hose 6/8 mm, AF 27, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	120.72
Article number	110792
EAN/barcode	 4047322022255
Your price	5,72 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	6/8 mm
Knurled nut	Polypropylene (PP)
L1	42.0 mm
L2	21.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK741
Screw fitting body	Polyamide (PA)
Thread	G 1/2
a/f	27 mm

Variants

Article number	Thread	For hose	a/f	Price
110792	G 1/2	6/8 mm	27 mm	5,72 € / Stk
110779	G 1/8	4/6 mm	14 mm	1,63 € / Stk
110780	G 1/8	6/8 mm	17 mm	2,92 € / Stk
110781	G 1/8	8/10 mm	19 mm	4,45 € / Stk
110782	G 1/8	9/12 mm	22 mm	8,66 € / Stk
110783	G 1/4	4/6 mm	17 mm	2,29 € / Stk
110784	G 1/4	6/8 mm	17 mm	3,69 € / Stk
110785	G 1/4	8/10 mm	19 mm	4,86 € / Stk
110786	G 1/4	9/12 mm	22 mm	10,86 € / Stk
110787	G 3/8	4/6 mm	22 mm	3,78 € / Stk
110788	G 3/8	6/8 mm	22 mm	5,08 € / Stk
110789	G 3/8	8/10 mm	22 mm	6,39 € / Stk
110790	G 3/8	9/12 mm	22 mm	8,32 € / Stk
110791	G 1/2	4/6 mm	27 mm	4,92 € / Stk
110793	G 1/2	8/10 mm	27 mm	6,85 € / Stk
110794	G 1/2	9/12 mm	27 mm	9,12 € / Stk

More Pictures

