


Datasheet for: 113010


Cross-piece 180, 4 x IT, Rp 3/4, black malleable cast iron

Cross-piece 180, 4 x IT, Rp 3/4, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFK 180-34
Article number	113010
EAN/barcode	 4047322251969
Your price	5,75 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK859
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 3/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113010	Rp 3/4	5,75 € / Stk
113011	Rp 1	7,18 € / Stk
113007	Rp 1/4	3,60 € / Stk
113014	Rp 2	19,41 € / Stk
113009	Rp 1/2	3,95 € / Stk
113013	Rp 1 1/2	12,94 € / Stk
113012	Rp 1 1/4	9,69 € / Stk
113008	Rp 3/8	3,95 € / Stk
113015	Rp 3	47,79 € / Stk