


## Datasheet for: 101515


**Pressure reducing valve, G 1/4 i. / o., Set pressure 8 bar**

Pressure reducing valve, G 1/4 interior / exterior, AF 17, Set pressure 8 bar, Input pressure max. 15 bar, Material: Brass . Industry, trade and repair shops often require working pressures of 15 bar or less. These pressure reducing valves, which are screwed directly onto the tool, enable that the pressure can be reduced to the selected working pressure. Benefits: - Significantly reduced risk of accidents - Longer tool life with fewer malfunctions - Lower noise levels at the workplace

Type number	637.08
Article number	101515
EAN/barcode	 4047322386739
Your price	13,64 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	34.0 mm
B	9.0 mm
C Ø	17.0 mm
Connecting thread	G 1/4 female / male
Flow rate	420 l/min
Housing	Brass
Max. input pressure	15 bar
Page No.	HK178
Set pressure	8.0 bar
a/f	17 mm

**Variants**

Article number	Set pressure	Flow rate	Price
101515	8.0 bar	420 l/min	13,64 € / Stk

## Variants

Article number	Set pressure	Flow rate	Price
101510	3.0 bar	360 l/min	9,39 € / Stk
101511	4.0 bar	380 l/min	9,39 € / Stk
101512	5.0 bar	390 l/min	9,39 € / Stk
101513	6.0 bar	405 l/min	9,39 € / Stk
101509	2.0 bar	300 l/min	9,68 € / Stk
101514	7.0 bar	415 l/min	12,77 € / Stk

## More Pictures

