


Datasheet for: 103120


Ball valve, Basic design, IT/ET, nickel-plated brass, G 3/4

Ball valve, Butterfly handle, Basic design, IT/ET, nickel-plated brass, Operating temp. -20 °C to 150 °C, G 3/4, PN max. 40 bar . Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems and air conditioning systems.

Type number	329.55-R
Article number	103120
EAN/barcode	 4047322400060
Your price	13,66 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	62.0 mm
B	47.0 mm
Ball	Chrome-plated brass
Ball seal	PTFE
Butterfly handle	Aluminium, painted red
DN	20.0
E	13.5 mm
F	12.5 mm
L	66.5 mm
Material	Nickel-plated brass
Operating temperature	-20 °C to 150 °C (no steam)
PN	40 bar
Page No.	HK268
Standard thread	G-thread acc. to DIN EN ISO 228-1, tolerance class B
Stem seal	NBR / FKM (Seal package consists of 2 O-rings)
Thread	G 3/4
Thread material	Bright brass

Variants

Article number	Thread	DN	PN	Price
103120	G 3/4	20.0	40 bar	13,66 € / Stk
103117	G 1/4	8.0	50 bar	8,99 € / Stk
103121	G 1	25.0	40 bar	20,00 € / Stk
103118	G 3/8	10.0	50 bar	9,13 € / Stk
103119	G 1/2	15.0	50 bar	9,79 € / Stk
103122	G 1 1/4	32.0	30 bar	32,24 € / Stk

More Pictures

