


## Datasheet for: 107223

**Quick-connect coupling I.D. 7.2, bright brass, rigid, Conn. 8x6**


Quick-connect coupling I.D. 7.2, bright brass, rigid, Connection 8x6, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, workshops, automotive.

Type number	243.320
Article number	107223
EAN/barcode	 4047322285230
Your price	13,66 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	Hose connection 8x6
DN	7.2
Flow rate	1000 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	132.0 mm
Locking pins	Stainless steel
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK533

Page No. SK	SK016
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Valve body	Brass with a bare metal surface
Version	Rigid
a/f	21 mm

## Variants

Article number	Version	Connection	Length	a/f	Price
107223	Rigid	Hose connection 8x6	132.0 mm	21 mm	13,66 € / Stk
107226	Swivelling 360°	Hose connection 8x6	132.0 mm	22 mm	15,67 € / Stk
107227	Swivelling 360°	Hose connection 10x8	143.0 mm	22 mm	18,89 € / Stk
107224	Rigid	Hose connection 10x8	143.0 mm	21 mm	14,02 € / Stk
107228	Swivelling 360°	Hose connection 12x9	150.0 mm	22 mm	20,81 € / Stk
107225	Rigid	Hose connection 12x9	150.0 mm	21 mm	14,35 € / Stk

## More Pictures

