

Datasheet for: 158917


Adjustable male conn., M20x1.5o., Pipe ext.Ø14, galvanised steel

Adjustable male connector, with cone seal, M20x1.5 o., Pipe exterior Ø 14, PN 630, a/f1 27, a/f2 27, galvanised steel .

| | |
|----------------|--|
| Type number | EGEM2014SSTKEG |
| Article number | 158917 |
| EAN/barcode |  4047322635790 |
| Your price | 13,74 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | | |
|---------------|-----|-----------------------------|
| Female thread | nut | M22x1.5 |
| L1 | | 50.5 mm |
| L2 | | 14.0 mm |
| Material | | Galvanised steel (DIN 2353) |
| PN | | 630 bar |
| Page No. | | HK824 |
| Thread | | M20x1.5 |
| Tube O.D. | | 14 mm |
| a/f 1 | | 27.0 mm |
| a/f 2 | | 27.0 mm |

Variants

| Article number | Female nut thread | Thread | Tube O.D. | PN | a/f 1 | a/f 2 | Price |
|----------------|-------------------|---------|-----------|---------|---------|---------|---------------|
| 158917 | M22x1.5 | M20x1.5 | 14 mm | 630 bar | 27.0 mm | 27.0 mm | 13,74 € / Stk |
| 158916 | M20x1.5 | M18x1.5 | 12 mm | 630 bar | 24.0 mm | 24.0 mm | 7,06 € / Stk |
| 158918 | M24x1.5 | M22x1.5 | 16 mm | 400 bar | 27.0 mm | 30.0 mm | 9,53 € / Stk |

Variants

| Article number | Female nut thread | Thread | Tube O.D. | PN | a/f 1 | a/f 2 | Price |
|----------------|-------------------|---------|-----------|---------|---------|---------|---------------|
| 158919 | M30x2.0 | M27x2.0 | 20 mm | 400 bar | 32.0 mm | 36.0 mm | 14,46 € / Stk |
| 158915 | M18x1.5 | M16x1.5 | 10 mm | 630 bar | 22.0 mm | 22.0 mm | 6,76 € / Stk |
| 158920 | M36x2.0 | M33x2.0 | 25 mm | 400 bar | 41.0 mm | 46.0 mm | 22,33 € / Stk |
| 158914 | M16x1.5 | M14x1.5 | 8 mm | 630 bar | 19.0 mm | 19.0 mm | 6,59 € / Stk |
| 158913 | M14x1.5 | M12x1.5 | 6 mm | 630 bar | 17.0 mm | 17.0 mm | 6,37 € / Stk |

More Pictures

