


Datasheet for: 103803



Throttle check valve, in block shape, Anodised aluminium, G 1/8

Throttle check valve, in block shape, Anodised aluminium, Operating temperature -10 °C to 70 °C, G 1/8, PN max. 10 bar . These valves are restricted in the flow direction and have free passage in the opposite direction.

Type number	225.33
Article number	103803
EAN/barcode	 4047322040594
Your price	10,23 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	34.0 mm
C	16.0 mm
E	24.0 mm
Housing	Anodized aluminium
I	15.0 mm
Internal parts	Brass
L	4.5 mm
M	16.4 mm
Max. operating pressure	10 bar
Max. operating temperature	70 °C
Min. operating temperature	-10 °C
Page No.	HK351
Sealant	NBR
Thread	G 1/8
Thread for panel mounting	M12x0.75
a/f	15 mm

Variants

Article number	Thread	a/f	Thread for panel mounting	Price
103803	G 1/8	15 mm	M12x0.75	10,23 € / Stk
103802	M5	11 mm	M9x0.75	12,00 € / Stk
103804	G 1/4	22 mm	M18x1.5	11,56 € / Stk
103805	G 3/8	22 mm	M18x1.5	18,63 € / Stk
103806	G 1/2	26 mm	M22x1.5	22,25 € / Stk

More Pictures

