


Datasheet for: 108960


Push-in L-fitting »metallica«, G 3/8 o., for hose exterior Ø 10

Push-in L-fitting »metallica«, G 3/8 o., for hose exterior Ø 10 mm, Working pressure max. 16 bar, nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

| | |
|----------------|--|
| Type number | 863.038-10 |
| Article number | 108960 |
| EAN/barcode |  4047322391207 |
| Your price | 10,25 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|---------------------|
| Clamping ring | Stainless steel |
| For tube O.D. | 10 mm |
| L1 | 28.0 mm |
| L2 | 36.0 mm |
| Material | Nickel-plated brass |
| Max. operating temperature | 150 °C |
| Max. working pressure | 16 bar |
| Min. operating temperature | -20 °C |
| Page No. | HK715 |
| Series | metallica |
| Sleeve | Nickel-plated brass |
| Thread | G 3/8 |
| a/f | 19 mm |

Variants

| Article number | Thread | For tube O.D. | a/f | Price |
|----------------|--------|---------------|-------|---------------|
| 108960 | G 3/8 | 10 mm | 19 mm | 10,25 € / Stk |
| 108958 | G 1/4 | 10 mm | 17 mm | 6,71 € / Stk |
| 108955 | G 1/8 | 8 mm | 14 mm | 5,20 € / Stk |
| 108957 | G 1/4 | 8 mm | 17 mm | 6,13 € / Stk |
| 108953 | G 1/8 | 4 mm | 14 mm | 5,13 € / Stk |
| 108956 | G 1/4 | 6 mm | 17 mm | 6,10 € / Stk |
| 108954 | G 1/8 | 6 mm | 14 mm | 5,13 € / Stk |
| 108961 | G 3/8 | 12 mm | 19 mm | 11,76 € / Stk |
| 108959 | G 3/8 | 8 mm | 19 mm | 9,58 € / Stk |
| 108952 | M5 | 6 mm | 8 mm | 4,95 € / Stk |
| 108951 | M5 | 5 mm | 8 mm | 4,71 € / Stk |
| 108950 | M5 | 4 mm | 8 mm | 4,61 € / Stk |
| 108962 | G 1/2 | 12 mm | 24 mm | 14,50 € / Stk |

More Pictures

