

## Datasheet for: 107091



### Quick-connect coupl. I.D. 2.7, nickel-plated brass, Sleeve I.D. 3

Quick-connect coupling I.D. 2.7, nickel-plated brass, Sleeve I.D. 3, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . One-hand quick disconnect couplings, one side sealing, extremely compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive.

Type number	243.08/5-N
-------------	------------

Article number	107091
----------------	--------

EAN/barcode	 4047322057998
-------------	--



4047322057998

Your price	8,05 € / Stk
------------	--------------

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

Ball	Stainless steel
Connection	I.D. 3
DN	2.7
Flow rate	165 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Nickel-plated brass
Length	35.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK520
Page No. SK	SK006
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Nickel-plated brass
Spring	Stainless steel

Valve body

Nickel-plated brass

## Variants

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107091	I.D. 3	8,05 € / Stk
107092	I.D. 4	8,05 € / Stk

## More Pictures

