


Datasheet for: 107856


Jaw coupling with exterior thread, G 3/4, with brass seal

Jaw coupling with ET, G 3/4, with brass seal, Malleable cast iron, galvanised / yellow passivated, Operating pressure max. 10 bar . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KA 34 M
Article number	107856
EAN/barcode	 4047322258975
Your price	10,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	17.0
H	63.0 mm
L	50.0 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK611
Sealant	NBR
Thread	G 3/4
a/f	32 mm

Variants

<i>Article number</i>	<i>DN</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
107856	17.0	G 3/4	32 mm	10,34 € / Stk
107855	11.0	G 1/2	27 mm	9,97 € / Stk
107857	17.0	G 1	40 mm	11,65 € / Stk