


Datasheet for: 114426


Bleeder valve, Standard nozzle, straight design, Sleeve I.D. 13

Bleeder valve, Aluminium, with standard nozzle, straight design, Temp. range -20 °C to 100 °C, PN max. 12 bar, Sleeve I.D. 13 . Robust, ergonomic blow-off valve for continuous duty under extreme conditions.

| | |
|----------------|--|
| Type number | 21 C |
| Article number | 114426 |
| EAN/barcode |  4047322263535 |
| Your price | 13,87 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------|---------------|
| Max. operating pressure | 12 bar |
| Max. temperature range | 100 °C |
| Min. temperature range | -20 °C |
| Nozzle | G 3/8 |
| Page No. | HK961 |
| Type of connection | Stem, I.D. 13 |

Variants

| Article number | Type of connection | Price |
|----------------|--------------------|---------------|
| 114426 | Stem, I.D. 13 | 13,87 € / Stk |

Variants

| <i>Article number</i> | <i>Type of connection</i> | <i>Price</i> |
|-----------------------|----------------------------------|---------------|
| 114424 | Stem, I.D. 6 | 13,87 € / Stk |
| 114427 | Push-in plug for DN 7.2 coupling | 13,87 € / Stk |
| 114428 | thread G 1/4 IT | 12,46 € / Stk |
| 114425 | Stem, I.D. 9 | 13,87 € / Stk |