


Datasheet for: 114427



Bleeder valve, Standard nozzle straight design, I.D. 7.2

Bleeder valve, Aluminium, Standard nozzle straight design, Temp. -20 °C to 100 °C PN max. 12 bar, Nipple for couplings I.D. 7.2 . Robust, ergonomic blow-off valve for continuous duty under extreme conditions.

Type number	21 K
Article number	114427
EAN/barcode	 4047322263542
Your price	13,87 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Max. operating pressure	12 bar
Max. temperature range	100 °C
Min. temperature range	-20 °C
Nozzle	G 3/8
Page No.	HK961
Type of connection	Push-in plug for DN 7.2 coupling

Variants

Article number	Type of connection	Price
114427	Push-in plug for DN 7.2 coupling	13,87 € / Stk

Variants

<i>Article number</i>	<i>Type of connection</i>	<i>Price</i>
114424	Stem, I.D. 6	13,87 € / Stk
114426	Stem, I.D. 13	13,87 € / Stk
114428	thread G 1/4 IT	12,46 € / Stk
114425	Stem, I.D. 9	13,87 € / Stk