


Datasheet for: 133816


Fitting 331 flat sealing R 3/4, Rp 3/4 black malleable iron fitting

Fitting 331, flat sealing, R 3/4, Rp 3/4, black malleable iron fitting, operating temp. -20 °C to 200 °C, ISO 7-1 . Maximum temperature and maximum operating pressure should not occur at the same time! According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Type number	TFV 331-34-DS
Article number	133816
EAN/barcode	 4047322480376
Your price	5,86 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	200 °C
Min. temperature range	-20 °C
Page No.	HK871
Standard thread	acc. ISO 7-1
Surface	Black
Thread	Rp/R 3/4

Variants

Article number	Thread	Price
133816	Rp/R 3/4	5,86 € / Stk

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133821	Rp/R 2 1/2	43,13 € / Stk
133817	Rp/R 1	7,25 € / Stk
133820	Rp/R 2	18,89 € / Stk
133819	Rp/R 1 1/2	12,24 € / Stk
133815	Rp/R 1/2	4,60 € / Stk
133818	Rp/R 1 1/4	9,89 € / Stk