

Datasheet for: 108893


Straight push-in fitting »metallica« R 1/2 o., hose exterior Ø 12

Straight push-in fitting »metallica«, R 1/2 o., for hose exterior Ø 12 mm, Working pressure max. 16 bar, nickel-plated brass . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

| | |
|----------------|--|
| Type number | 844.012-12 |
| Article number | 108893 |
| EAN/barcode |  4047322390682 |
| Your price | 5,93 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|---------------------|
| Clamping ring | Stainless steel |
| For tube O.D. | 12 mm |
| L1 | 33.0 mm |
| Material | Nickel-plated brass |
| Max. operating temperature | 150 °C |
| Max. working pressure | 16 bar |
| Min. operating temperature | -20 °C |
| Page No. | HK713 |
| Series | metallica |
| Sleeve | Nickel-plated brass |
| Thread | R 1/2 |
| a/f | 22 mm |

Variants

| Article number | Thread | For tube O.D. | a/f | Price |
|----------------|--------|---------------|-------|--------------|
| 108893 | R 1/2 | 12 mm | 22 mm | 5,93 € / Stk |
| 108891 | R 3/8 | 10 mm | 17 mm | 3,62 € / Stk |
| 108884 | R 1/8 | 8 mm | 13 mm | 2,86 € / Stk |
| 108890 | R 3/8 | 8 mm | 17 mm | 3,62 € / Stk |
| 108887 | R 1/4 | 8 mm | 13 mm | 2,99 € / Stk |
| 108886 | R 1/4 | 6 mm | 14 mm | 2,99 € / Stk |
| 108888 | R 1/4 | 10 mm | 16 mm | 3,62 € / Stk |
| 108883 | R 1/8 | 6 mm | 11 mm | 2,68 € / Stk |
| 108882 | R 1/8 | 4 mm | 10 mm | 2,68 € / Stk |
| 108885 | R 1/4 | 4 mm | 14 mm | 3,22 € / Stk |
| 108892 | R 3/8 | 12 mm | 17 mm | 4,39 € / Stk |
| 108889 | R 1/4 | 12 mm | 17 mm | 4,83 € / Stk |

More Pictures

