


Datasheet for: 107143


Quick-connect coupling I.D. 5, bright brass, rotating, Hose connection 6x4

Quick-connect coupling I.D. 5, bright brass, rotating, Hose connection 6x4, Operating pressure - 35 bar, Temp. -20 °C to 100 °C . One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. Areas of application: Pneumatic system, measurement, monitoring and control systems, manufacturing industry, medical technology, chemical / pharmaceutical industry, automotive, food technology.

Type number	243.37
Article number	107143
EAN/barcode	 4047322285476
Your price	10,49 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Connection	Hose connection 6x4
DN	5
Flow rate	560 l/min (air)
Flow rate measurement	at 6 bar and $\Delta p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	134.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	to 35 bar, maximum static working pressure (non-pulsating)
Page No.	HK525
Page No. SK	SK009
Retaining ring	Stainless steel
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel

Valve body
 Version
 a/f

Brass with a bare metal surface
 Swivelling 360°
 14 mm

Variants

Article number	Version	Connection	Length	Price
107143	Swivelling 360°	Hose connection 6x4	134.0 mm	10,49 € / Stk
107141	Rigid	Hose connection 6x4	120.0 mm	6,37 € / Stk
107142	Rigid	Hose connection 8x6	132.0 mm	6,37 € / Stk
107144	Swivelling 360°	Hose connection 8x6	145.0 mm	10,49 € / Stk

More Pictures

