


Datasheet for: 107758



GEKA hose piece, rigid, bright brass, Connection I.D. 32

GEKA hose piece, rigid, bright brass, Connection I.D. 32, Operating pressure max. 40 bar, Medium / ambient temp. -10 °C to 90 °C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 106
Article number	107758
EAN/barcode	 4047322132848
Your price	8,16 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	I.D. 32
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK607
Sealant	NBR

Variants

Article number	Connection	Price
107758	I.D. 32	8,16 € / Stk
107753	I.D. 10	4,58 € / Stk
107754	I.D. 13	4,26 € / Stk
107755	I.D. 16	5,34 € / Stk
107756	I.D. 19	4,84 € / Stk
107757	I.D. 25	5,89 € / Stk
107759	I.D. 38	10,54 € / Stk